

Steps for Brewing Coffee

1. Place (1) filter into brew basket
2. Place one pre-measured packet of coffee into the filter
3. Slide the brew basket into holder
4. Place the appropriate empty decanter (regular or decaf) into position below the brew basket
 - *NOTE: First open lid on decanter (to open lid depress the two buttons located on the sides of the lid and lift upwards) and ensure the decanter is empty.*



5. Press the appropriate brew start switch - # 1 is the correct switch for a full pot
 - Ensure the READY light is on before starting the brew cycle



6. Do not remove decanter during the brewing process
 - Brew cycle may be canceled by depressing any brew button or the cancel switch on the front control panel
 - Hot water will be delivered through the spray head
 - The coffee brew will drain from the brew basket into the decanter below
7. The Brewing light should continue to flash until all the liquid has finished flowing from the brew basket
 - **CAUTION: HOT LIQUIDS MAY REMAIN IN THE BREW BASKET AFTER THE BREWING LIGHT IS OFF! DO NOT REMOVE THE BREW BASKET UNTIL ALL THE LIQUID HAS FINISHED FLOWING FROM THE BREW BASKET.**
 - Do not remove decanter until the brewing process has stopped and all liquid has stopped
8. To clean brew basket simply remove from brew rails and dump filter into waste basket
 - The brewing process, as described above, can now be started again

CUSTOMER SERVICE OR MACHINE REPAIR REQUESTS:

Call 1-800-747-8363 or email gethelp@canteenone.com

COFFEE PREPERATION PROCEDURES- NEWCO GXDF2-15 BREWER

1) Place filter into brew basket.

2) Put the appropriate amount of ground coffee into the filter for the volume of coffee being brewed.

3) Slide the brew basket into holder.

4) Set the volume selection switch to the appropriate position for the volume of coffee being brewed.

5) For warmer units:

Place empty decanter on warmer located directly under the brew basket.

Turn corresponding warmer switch to ON position.

For dispenser units:

Remove the dispenser lid unless it is a brew through design.

Place the dispenser directly under the brew basket.

6) Press brew start/stop switch. Note: a brew cycle may be initiated even if the heating light is on.

7) If the autoarm feature is enabled the heating light will begin to flash indicating that the brewer is heating and will begin to brew immediately after the heating cycle is complete. Do not remove decanter. Brew cycle may be canceled by depressing the brew start/stop switch. The heating light should no longer be flashing.

8) Hot water will be delivered through the sprayhead. This distributes the hot water evenly over the coffee bed within the brew basket. The coffee brew will drain from the brew basket into the decanter below.

9) The status brewing light should continue to flash until all the liquid has finished flowing from the brew basket. Do not remove decanter until the brewing process has stopped and all liquid has stopped flowing from the brewbasket.


10) The resultant coffee brew should be crystal clear and have the desired properties attainable through excellent extraction.

11) To clean brew basket simply remove from brew rails and dump filter into wastebasket. The brewing process, as described above, can now be started again.




NESPRESSO MOMENTO 100 INSTRUCTIONS


COFFEE

- 1 Ensure slot is empty — select capsule and drop into slot above brew head
 - Manually flatten capsule edges 
 - Drop in only one capsule
- 2 Choose desired coffee size, place appropriate cup under brew head and touch screen to brew
 - Move the cup support to the side if a large cup is used
 - Recommended recipes are highlighted on screen



HOT WATER

- *  With cup under brew head, touch screen for preset amount (10 oz standard)

NOTE: Machine will be preprogrammed with between 3 and 5 of the coffee sizes shown above. During any product preparation, press  to stop dispensing.







ZENIUS INSTRUCTIONS



ESPRESSO

- 1  Press power and wait until lights stop blinking
- 2 Make sure handle is in an upright position
- 3 Ensure slot is empty — select capsule and insert into slot
 - Manually flatten capsule edges 
 - Insert only one capsule
- 4 Gently pull handle down
- 5 Choose desired coffee size, place appropriate cup under brew head and press button once to brew



RISTRETTO
.85oz



ESPRESSO
1.35oz



LUNGO
3.75oz

NOTE: When finished, return handle to upright position to eject capsule

HOT WATER

- *  Press for preset amount (4 oz standard)